

DRIVEWAY REQUIREMENTS

SEC. 82-248. SPECIAL REQUIREMENTS FOR RESIDENTIAL DRIVEWAYS.

The following are applicable to driveways serving residential property:

(1) *Width of driveways.* Openings for vehicular ingress and egress shall be at least ten feet wide at the property line for residential properties, but shall not exceed three feet wider than the garage door opening or 24 feet, whichever is greater, at the property line, with a maximum additional six feet at the curb opening.

(2) *Angular placement.* The centerline of the drive may be parallel to the line of the lot where access is required or at right angles to the curblines.
(Code 1988, § 6-3-2(c))

SEC. 82-249. APPEAL FROM PERMIT REFUSAL.

Any person feeling aggrieved by the refusal of the building inspector to issue a permit for a private driveway may appeal such refusal to the board of appeals within 20 days after such refusal to issue the permit is made.

(Code 1988, § 6-3-2(d))

SEC. 82-250. PROHIBITED DRIVEWAYS.

(a) No person shall place, construct, locate, or cause to be placed, constructed or located any obstruction or structure within the limits of any public road, highway or street in the village except as permitted by this division. As used in this subsection, the term "structure" includes private driveways, a portion of which extends into any public road, highway or street, and which is in nonconformance with this article.

(b) No driveway shall be closer than ten feet to the extended street line at an intersection. At street intersections a driveway shall not provide direct ingress or egress to or from the street intersection area and shall not occupy areas of the roadway deemed necessary by the village for effective traffic control or for highway signs or signals.

(c) The grade of that portion of any private driveway or pedestrian path located within the limits of any public road, highway or street shall be such as shall meet the grade of the existing public roadway at its edge and shall not cause an obstruction to the maintenance or clearing of such public roadway.

(d) No driveway apron shall extend out into the street further than the facing of the curb, and under no circumstances shall such driveway apron extend into any gutter area. All driveway entrances and approaches shall be constructed as not to interfere with the drainage of streets, side ditches or roadside areas, or with any existing structure on the right-of-way.

(e) No portion of any curb, parapet or retaining wall, rising above the grade of the driveway, erected by the owner of the premises involved, shall extend beyond the culvert spanning the watercourse located in such public way. (Code 1988, § 6-3-2(e))

DRIVEWAY

MINIMUM 10 Feet- MAXIMUM 24 Feet

Propert Line

4 inches
of concrete

SIDEWALK

6 inches of concrete

4 inches of concrete

6 Inches of concrete

CURB OPENING MAXIMUM 30 Feet

CURB LINE

ROADWAY

